

# Declaration of performance

Nr.: sat-0009-p4-hnka-a1-210831

Technical insulation slab out of glass wool, with/without facing Vn/Vnl/Vs/Vsl/G, continuously water-repellent

1	Unique identification code of the product-type	SAGLAN T-SA-K 30
2	Type, batch or serial number or any other element	See product label
3	Intended use or uses of the construction product	Thermal insulation materials for technical building equipment and industrial installations in industry (ThlBEII)
4	Manufacturer	Sager AG, Dornhügelstrasse 10, CH-5724 Dürrenäsch
5	Authorised representative	Not applicable
6	System or systems as set out in CPR, Annex V.	System 3; System 1
7	The notified body, which issued a certificate of consistency of performance	FIW München, (identification number 0751)

8	Essential characteristics						Performance		Harmonised standard	
	Reaction to fire		Reaction to fire		Thickness 25-120 mm		Euroclass	A1	EN 14303:2009+A1: 2013  NPD= No performance determined	
	Acoustic absorption index		Sound absorption				NPD			
	Thermal resistance*	Thermal conductivity W/mK	9 °C	10	50	100	150	200		250
			λ <sub>D</sub>	0.035	0.042	0.053	0.065	0.079		0.097
		Thicknesses	d <sub>N</sub> = 25mm - 120mm			Thickness classes		T3		
	Water permeability		Water absorption				WS1	≤1.0kg/m2		
	Water vapour permeability		Water vapour transmission μ				1			
	Compressive strength		Compressive strength				NPD			
	Rate of release of corrosive substances		Trace quantities of watersoluble ions and the pH-value				NPD			
	Release of dangerous substances to the indoor environment		Release of dangerous substances				NPD	(e)		
	Continuous glowing combustion		Continuous glowing combustion				NPD	(a)		
	Durability of thermal resistance against heat, weathering, ageing/degradation						NPD	(c)		
	Durability of reaction to fire against heat, weathering, ageing/degradation						NPD	(b)		
Durability at high temperatures by influence of fire						NPD	(d)			
Durability of thermal resistance against high temperatures						Upper limit of use temperature ST(+/-250)250(=250°C)				

\* Dimensions and associated thermal resistance, see product data sheets under [www.sager.ch](http://www.sager.ch)

- a) A European test method is under development and the standard will be amended when this is available.
- b) Durability: The fire performance and thermal conductivity of mineral wool does not deteriorate with time. The Euroclass classification of the product is related to the organic content, which cannot increase with time.
- c) The thermal conductivity of mineral wool does not deteriorate with time. Experience has shown the fibre structure to be stable and the porosity contains no other gases than atmospheric air.
- d) At high temperatures there is no deterioration of the Fire reaction for products from Mineral wool. The classification of the product into a particular euro class refers to the content of organic components, which remain the same at high temperatures or decrease.
- e) See Safe Use Instruction Sheet

\* Possible one-sided or two-sided facings:

Vn: Natural glass fibre fleece

G: Black glass fabric, fungicide-treated

Vnl: Natural glass fibre fleece long, reinforced

Vs: Black glass fibre fleece

Vsl: Black glass fibre fleece, long, Reinforced

9	The performances of the products identified in points 1 and 2 are in conformity with the declared performances in point 8.
	This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

10	Signed in the name of the manufacturer from Beat Bruderer, Managing director
	Place and date Dürrenäsch, 31. August 2021
	Signature: 