

Declaration of Performance

No.: sa-0004-si25-rak-a1-180130



According to Article 4 of the Building Products Directive (EU Building PVO) 305/2011

1	Unique identification code of the product-type	Saglan SI 25, insulation role (with alu facing)
2	Type, batch or serial number or any other element	See product label
3	Intended use or uses of the construction product	Thermal insulation for buildings (ThlB)
4	Manufacturer	Sager AG, Dornhügelstrasse 10, CH-5724 Dürrenäsch
5	Authorised representative	Not applicable
6	System or systems as set out in CPR, Annex V.	System 3; System 1
7	The notified body, which issued a certificate of consistency of performance	FIW München (identification number 0751)

8	Declared performance				
	Essential characteristics	Performance			Harmonised standard
	Thermal resistance	Thermal resistance R_D	m2K/W	(d)	EN 13162:2012 +A1:2015 NPD = No Performance Determined
		thermal conductivity λ_D	W/mK	0.035	
		thickness d_N ; thickness tolerance	mm	20-60, T3	
	Reaction to fire	Reaction to fire	A1		
	Durability of reaction to fire against heat, weathering, ageing/degradation	Durability characteristics	A1	(b)	
	Durability of thermal resistance against heat, weathering, ageing/degradation	Thermal resistance	R_D	(c)	
		Thermal conductivity	λ_D	(c)	
		dimensional stability	DS (70,-)	≤1%	
	Compressive strength	Compressive strength	CS 10	NPD	
		Point load		NPD	
	Tensile/flexural strength	Tensile strength perpendicular to the plate plane		NPD	
	Durability of reaction to fire against heat, weathering, ageing/degradation	Compressive creep	(b)	NPD	
	water permeability	short-term water absoption	WS	NPD	
	Water vapour permeability	water vapor diffusion	MU	100	
	Impact sound transmission (Floors)	Dynamic stiffness		NPD	
		Thickness d_L		NPD	
		Compressibility		NPD	
		Air flow resistivity		NPD	
	Acoustic absorption index	Sound absorption		NPD	
	Direct airborne sound insulation index	Air flow resistivity	Afr.	>5kPa s/m2	
	Release of dangerous substances, emission to the interior of the building	Release of dangerous substances	(a)	NPD	
	Continous glowing combustion	Continous glowing combustion	(a)	NPD	

- a) A European test method is under development and the standard will be amended when this is available.
- b) Durability: The fire performance and thermal conductivity of mineral wool does not deteriorate with time. The Euroclass classification of the product is related to the organic content, which cannot increase with time.
- c) The thermal conductivity of mineral wool does not deteriorate with time. Experience has shown that fibre structure to be stable and the porosity contains no other gases than atmospheric air.

d)	Thickness in mm	20	25	30	40	50	60
	Declared thermal resistance R_D	0.55	0.70	0.85	1.10	1.40	1.70

9	The performances of the products identified in points 1 and 2 are in conformity with the declared performances in point 8.
	This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

10	Signed in the name of the manufacturer from Marc Lüdi, Managing director
	Place and date: Dürrenäsch, 30. January 2018 Signature: